

TECHNICAL DATA

Art. ISABELLA IMPERMEABLE / ENDUIT 160cm Teflon



Composition: 100% acrylic Dralon

Composition final: 91% Dralon / 9% Acrylique

Warp: 25 thread/cm, 100% acrylic Dralon - yarn dyed - count NM 34/2

Weft: 12 thread/ cm, 100% acrylic Dralon - yarn dyed - count NM 20/1

Width: h.cm. 160

Gr./mq: 230 gr/mq2 (+/- 5%)

\*Light fastness to light UNI EN ISO 105-B02:2004: 6/7 degree

\*colour fastness to water UNI EN ISO 105-E01:2013: 4/5

\*colour fastness to sea and chlorate water UNI EN ISO 105-E02+E03: 4/5

\*water column UNI EN 20811:1993: 22/25 CM

\*breaking load UNI EN ISO 13934-1:2013:chaine: 1500N -- trame: 510N

\*martindale UNI EN ISO 12947-1/2:2000: > 60.000

Finishing: Teflon original + double enduction acrylique

Washing:



- IMMEDIATELY clean the stains with a sponge

- Iron on the right (face not coated), average temperature

- Do not use chlorine and fabric softener

- Do not use tumble dryer

- Hanging so that it drips in the shade

The coated side must not be exposed to the weather / sun, this guarantees a longer durability of the impermeability.

HS CODE : 59031090

\*\_Tests performed on the color ISABELLA UNI NOIR